

8346

Combination Units



FEATURES & BENEFITS

Safety

8" x 10-3/4" universal combination emergency sign and 21" self-adhesive high visibility stripe in Safety Green and bright yellow make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

Shower Head

AXION MSR™ ABS plastic drench shower head uses a hydrodynamic design to give equal distribution of water throughout the entire footprint of flow.

Construction

1-1/4" Schedule 40 hot-dipped galvanized steel pipe and fittings along with powder-coated cast-iron 9" diameter floor flange and 11" stainless steel receptor provide an additional corrosion resistance in a long lasting product.

Valves

Eye/face wash valve is designed to make the flushing of fluid remains occur with the simple push of a stainless steel flag. Shower ball valve is designed to make the flushing of fluid remains occur with the pull of a triangular lever.

Dust Cover

Stainless steel dust cover protects eye/face wash and spray ring as well as bowl up until the last second before use further optimizing operation.



Shown with SP829B shower head.

SPECIFICATIONS

Model 8346 combination shower and eye/face wash shall include the AXION MSR™ hydrodynamic designed ABS plastic showerhead with self-regulating 20 gpm flow control, stainless steel 11" round bowl, green Soft-Flo ABS plastic eyewash anti-surge heads and stainless steel face ring, polished stainless steel dust cover, chrome-plated brass in-line 50 x 50 mesh water strainer, and chrome-plated brass stay-open shower and eyewash ball valves equipped with stainless steel ball and stem. Unit shall also include powder-coated cast-iron 9" diameter floor flange, universal sign, self-adhesive high visibility safety green and bright yellow stripes, and 1-1/4" IPS supply.

OPTIONS

- Hose & Spray Unit: Model 8901RFK, body spray unit with Feather-Flo ABS plastic head, stay open squeeze lever valve, 8 foot hose, and installation kit.
- Tempered Water Blending Systems: Model TWBS.SH, prepackaged, fully engineered and tested system for mixing hot and cold water to provide tempered water up to 40 gpm for emergency showers and eyewashes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9202, thermostatic mixing valve that mixes hot and cold water for the tempering of shower units at a maximum flow rate of 40 gpm.
- Shower Head: Model 8127FC, corrosion-resistant 10-1/2" stainless steel showerhead with integral 20 gpm flow control.

To see all options for this model, visit www.hawsco.com.

APPLICATIONS

Where the eyes or body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching or flushing of the eyes and body shall be provided within the work area for immediate emergency use. Emergency eyewash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8346 is certified by CSA & IAPMO to meet the ANSI Z358.1-2004 Standard for Emergency Eyewash and Shower Equipment.

